

Multi-channel Singlemode Fiber Optic Rotary Joint

Model 291

Focal Technologies Corporation, a Moog Inc. company, has over 30 years of expertise in supplying standard and custom marine products for harsh environment applications and is a leading manufacturer of high performance and high quality fiber optic rotary joints. Contact Focal for any assistance in selecting the best solution for your requirements.



The FO291 is a multi-pass, singlemode fiber optic rotary joint (FORJ). It is passive and bidirectional, and allows the transfer of optical signals across a rotational interface on 2 to 9 separate singlemode optical fibers.

The FO291 can be combined with our electrical and / or fluid slip rings, giving a single, compact package for optical signals, electrical power and fluid transfer, with ISO 9000 quality.

Other options include fluid-filling for pressure compensation permitting operation at any ocean depth, and the combination of the model 190 to include up to a total of 19 multimode passes.

Features

- 2 to 9 singlemode channels
- Can be combined with our electrical slip rings, fluid rotary unions and the model 190 multimode fiber optic rotary joint
- Alternative drive coupling arrangements are available (consult factory for specification details)
- Tested to 10,000 psi (69,000 kPa) when fluid-filled
- Aluminum and stainless steel construction
- Connectorized interfaces, for easy fiber cable replacement
- Rugged design
 - MIL-STD-167-1 ship vibration
 - MIL-STD-810 functional shock (40g)

Benefits

- Can be integrated into existing slip ring designs
- Passive bidirectional optical transmission
- Can be combined with our electrical slips and fluid unions
- Long life

Applications

- Remotely operated vehicles
- Floating production systems
- Undersea telemetry
- Seismic streamers
- Radar antennas
- Cable reels

Specifications

| FO291 Specifications | | | | | | | | | |
|----------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|--------------|--------------|--------------|--------------|--------------|--------------|---------------|
| | Channel | 2-Pass | 3-Pass | 4-Pass | 5-Pass | 6-Pass | 7-Pass | 8-Pass | 9-Pass |
| Insertion Loss (dB) (Typical/Maximum, Includes Rotational Variation) | 1 | 2.0/3.0 | 2.0/3.0 | 2.0/3.0 | 2.0/3.0 | 2.0/3.0 | 2.0/3.0 | 2.0/3.0 | 2.0/3.0 |
| | 2 | 2.0/3.5 | 2.5/3.5 | 2.5/3.5 | 2.5/3.5 | 2.5/3.5 | 2.5/3.5 | 2.5/3.5 | 2.5/3.5 |
| | 3 | | 2.5/4.0 | 3.0/4.0 | 3.0/4.0 | 3.0/4.0 | 3.0/4.0 | 3.0/4.0 | 3.0/4.0 |
| | 4 | | | 3.0/5.0 | 3.5/5.0 | 3.5/5.0 | 3.5/5.0 | 3.5/5.0 | 3.5/5.0 |
| | 5 | | | | 3.5/5.5 | 4.0/5.5 | 4.0/5.5 | 4.0/5.5 | 4.0/5.5 |
| | 6 | | | | | 4.5/6.5 | 5.0/6.5 | 5.0/6.5 | 5.0/6.5 |
| | 7 | | | | | | 5.5/6.5 | 5.5/6.5 | 5.5/6.5 |
| | 8 | | | | | | | 6.0/6.5 | 6.0/6.5 |
| | 9 | | | | | | | | 6.0/6.5 |
| Variation Length "L", inch [mm] | | 3.82 [97.0] | 4.70 [119.4] | 5.59 [142.0] | 6.47 [164.3] | 7.36 [186.9] | 8.24 [209.3] | 9.13 [231.9] | 10.01 [254.3] |
| Rotational Variation | Typical < 1.0 dB, maximum < 2.0 dB | | | | | | | | |
| Back Reflection ¹ | Typical > 22dB, minimum > 18 dB | | | | | | | | |
| Wavelengths | Suitable for operation over full CWDM band (18 wavelengths from 1271nm to 1611nm in 20nm increments), tested at 1310nm and/or 1550nm. Consult factory for other wavelengths such as 900-1100nm band (tested at 1060nm) | | | | | | | | |
| Rotational Speeds | To 100 rpm dry and 60 rpm fluid filled. Consult factory for higher rotational speeds | | | | | | | | |
| Temperature | -40 to +60 °C standard. Consult factory for extended range | | | | | | | | |
| Exterior Surfaces | Stainless steel and aluminum | | | | | | | | |
| Vibration | Per MIL-STD-167-1A | | | | | | | | |
| Shock | 40 g / 11 ms sawtooth per MIL-STD-810 Method 516 | | | | | | | | |
| Connectors | FC / PC connector bushings standard (ST connector bushings optional) | | | | | | | | |
| Pressure | Up to 10,000 psi (69,000 kPa) for fluid filled version | | | | | | | | |

¹ Lower back reflection available, consult factory.

