

FO292

Fiber optic rotary joint

Description

The FO292 is an ultra-compact, two pass, multimode fiber optic rotary joint (FORJ). It is passive and bidirectional, and allows the transfer of optical signals on two separate optical fibers across rotational interfaces.

The FO292 can be combined with our electrical and fluid slip rings, giving a single, compact package for optical signals, electrical power and fluid transfer.

The FORJ can be assembled with pigtail lengths tailored to the customer's application. Housing, mounting flange and drive features can also be customized to meet the customer's requirements. The FO292 can also be installed with one or both ends having a 90° cable exit, providing even more flexibility when installing the unit into existing slip ring assemblies or installations with little clearance space.

Features

- Provides rotary coupling for two multimode fibers
- Passive and bidirectional
- Can be combined with various electrical slip rings and fluid unions
- Smaller and more compact than the standard FO215 with improved back reflection performance
- Customized mounting flanges available
- Optional 90 degree cable exits at either end of the FORJ
- Optional fluid-filled version for deep submergence to 10,000 psi (69,000 kPa)
- Can be integrated into existing slip ring designs
- Stainless steel housing
- Rugged design
 - MIL-STD-167-1 ship vibration
 - MIL-STD-810E functional shock (40 g)



Typical Applications

- Winches and cable reels for remotely operated vehicles
- Remote I / O in industrial machinery
- Video surveillance systems
- Material handling systems
- Sensor platforms
- Robots
- Turrets

Fiber Optic Rotary Joints (FORJ)

FO292 Specifications

Fiber Size (Microns)	50 / 125 or 62.5 / 125. Consult factory for other fiber types.		
Insertion Loss*		Typical	Maximum
	Channel 1	< 1.5 dB	< 3.0 dB
	Channel 2	< 4.5 dB	< 6.0 dB
Rotation Variation	Typical < 0.5 dB		Maximum < 1.0 dB
Back Reflection	Typical 20 dB		18 dB Minimum
Wavelengths	850, 1300 or 1550 nm. Consult factory for other multi-wavelength applications.		
Rotational Speeds	To 500 rpm. Higher rotational speeds should be discussed with the factory.		
Temperature	-40 to +60 deg C (dry version) -20 to +60 deg C (wet version) Consult factory for extended range.		
Dispersion	< 10 ps (calculated)		
Exterior Surfaces	Stainless steel		
Vibration	Tested to MIL-STD-167-1 (ships)		
Shock	Tested to MIL-STD-810F		
Terminations	Standard is with pigtail cables terminated with ST connectors at each end. Alternative connectors types available (FC, SC, LC).		
Pressure	Up to 10000 psi (69,000 kPa) for fluid filled version*		
Pigtail Length*	As required		

* Add 0.5 dB to the insertion loss to version with 90 degree cable exits.

* Fluid filled version is slightly larger than shown below.

Note: Optical values given are based on use with LED sources.

FO292 Dimensions

